



## 70 Series Electric Strikes

The **SDC 70 Series** electric strike is designed for use with cylindrical locks, mortise locks or mortise exit devices having up to .75" (19mm) throw latchbolts. The 70 series fits a standard ANSI 4.875" (124mm) frame preparation, with a modification.

### Features

- Tamper resistant heavy-duty construction
- All stainless steel for strength and corrosion resistance
- Horizontal keeper adjustment for misaligned doors and frames
- .75" keeper depth
- Non-handed, field reversible
- Failsecure (standard)    Failsafe (optional)

### Model

- 70-12** Square corner faceplate for hollow metal frames.  
**70-32** Square corner faceplate and an offset solenoid for wood frames or pair of wood doors.

### Electrical Specifications

Specify **12** or **24**  
 0.29 Amp, @ 12VDC, 41 OHMS  
 0.15 Amp, @ 24VDC, 160 OHMS

### Finish

- U 630** Satin Stainless Steel  
**D 606** Satin Brass  
**G 612** Satin Bronze  
**H 613** Oil Rubbed Bronze

### Options

- FS** Fail-Safe operation  
**LBM-70** .75" Latchbolt Monitor  
**LCM-70** Locking Cam monitor  
**BR64XL** Rectifier for AC operation  
**PC** Plug connector  
**MT** Pair of Mounting Tabs  
**AS** Astragal

### Listings

- Auxiliary locks and associated products
- ANSI / BHMA A156.5 - Grade 1
  - DoD FSC 5340
- Burglary Protection Equipment
- ANSI / UL1034 - Grade 1
- Fire Door Accessories (Fail-Secure only)
- UL Listed for fire door assemblies up to 3 hours. UL10B

### How to Order

Model	Volt	Finish	Options
70-12	24	U	LBM-70/PC/MT



70-12



70-32



Made in the USA



SECURITY DOOR CONTROLS

www.sdcsecurity.com E-mail: service@sdsecurity.com



